

## Reverse Osmose EDI

Series UP 4100 – UP 20000



### UP 4100 – UP 20000 UO and EDI Systems for ultra-pure water

Vertical frame system for desalination of softened drinking water operating on the principle of reverse osmosis(RO) in conjunction with the electro-deionization method (EDI).



Geonwater BV Centaurusweg 148-02 TILBURG  
T. +31 (0)13 533 44 69 E.geon@geonwater.nl

[www.geonwater.nl](http://www.geonwater.nl)

## UP 4100 – 20000 l/h

### RO + EDI Systems for ultra-pure water

**Unit design** Stainless steel main frame with plastic front panel housing the instruments and controls,

Special inlet filter with 5 µm filter cartridge, **high-pressure pump** low noise, multi-stage centrifugal type, **spirally wound modules** with high rejection PA/PS composite membranes in GRP vessels with inliner, permeate recirculation subject to conductivity.

**Electro-deionization module** for continuous desalination of the RO permeate, consisting of a carefully designed robust housing containing a series of special ion selective membranes which create alternating concentrate and desalination chambers filled with mixed-bed ion exchanges resins. Two special electrodes are used to create an DC electric field across the chambers.

**Valves** such as sampling valves for feed water, RO permeate and EDI product, inlet diaphragm valve, control valves made of stainless steel to regulate the flow rate of permeate, RO concentrate, RO concentrate and EDI concentrate.

**Pressure monitoring** vibration-resistant pressure gauges for inlet and outlet pressure, pre-filter, operating pressure, RO concentrate pressure, pressure EDI feed water, inlet pressure EDI concentrate, product output pressure, pressure switch for monitoring the feed water pressure,

**Flow meters** for permeate, RO concentrate, RO concentrate recirculation, EDI feed water, EDI concentrate, electrolyte, control of minimal EDI concentrate flow rate,

**Permeate conductivity measurement**, temperature compensated, measuring range 0 – 200 µS/cm,

**Product water resistivity measurement**, constant on-line with temperature compensation as defined by ASTM D 1125-95, measuring range 0 – 20 MΩ x cm.

**Control cabinet** with lockable main switch, **electrical switchgear** for control of the high-pressure pump, **integral power supply** for supply of voltage to the EDI module

**RO 1000 microprocessor control system** for fully automated monitoring and control of the system with two line text display (16 characters per line) for display of

**operational status:** permeate conductivity, temperature, operating hours, password-protected programming of the operating sequences.

**Malfunction displays** for low pressure feed motor overload, high conductivity.

**Additional connections:** Inputs (low voltage) for level control with 1 or 2 float switches, shut-down by external signal (forced stop, regeneration),

**Outputs** for Pretreatment (230 V/50 Hz), solenoid valves for permeate discard and -recycling, and DDC (collective malfunction signal on voltfree changeover contact).

Unit is completely wired, pre-assembled and ready for installation. Electrical equipment in accordance with VDE 0100 part 600, VDE part 1. Compressed air (oilfree, 4-6 bar) required.

**Options:** Membrane degassing, dosing stations, concentrate flushing unit KSE, pipeworks in PP on request

*The units are designed for softened feed water (< 0.1 °GH) with a maximum TDS of 1,000 mg/l, a water temperature of 15 °C, a maximum colloidal index of 3, a CO2 content of 10 mg/l and a SiO2 content of 20 mg/l. Under these conditions, the units still reach design product flow after three years of operation. The EDI product recovery depends on the raw water quality and the type of pre-treatment.*

Technical Data		UP 4100	UP 6000	UP 8200	UP 11000	UP 20000
Permeate flow rate	l/h	4100	6000	8200	11000	20000
Resistivity EDI product (with free CO <sub>2</sub> )	MΩ x cm	10	10	10	10	10
Recovery	%	70	70	70	70	70
Operating pressure	bar	18	18	18	18	18
Membrane element / number		8040/4	8040/54	8040/7	8040/9	8040/17
Voltage	V/Hz	3 x 400/50	3 x 400/50	3 x 400/50	3 x 400/50	3 x 400/50
Power consumption	kW	13,5	20	20	26	45
Pre-fusing max.	A	25	40	40	50	90
Feed water connection	DN	40	50	50	50	80
Product water connection	DN	32	40	40	50	65
Waste water connection	DN	1x32 / 1x20	1x32 / 1x20	1x32 / 1x20	1x32 / 1x20	1x50 / 1x20
Height	mm	2000	2000	2000	2200	2200
Width	mm	3000	4000	5000	4000	5000
Depth	mm	850	850	850	1000	1500
Weight approx	kg	700	800	850	1100	2000

*pH value feed water min./max 5.0 / 9.5, feed water pressure min./max. 2/4 bar, feed water temperature min./max. 5 /35 °C, ambient temperature max. 40 °C*

Geonwater BV Centaurusweg 148-02 TILBURG  
T. +31 (0)13 533 44 69 E.geon@geonwater.nl

[www.geonwater.nl](http://www.geonwater.nl)